

SWG 100 CEM

STATIONARY ANALYZER FOR CONTINUOUS EMISSION MONITORING

4-20mA

RS 485

PROFIBUS

ETHERNET

SD

ALARM



O₂

CO

CO₂

NO

NO₂

NO_x

SO₂

°F

Δ°F

ΔP

Draft

Pres-
sure

Flow



since 1984®

AIR fair

EMISSION MONITORING SYSTEMS

Over 30 years of innovative gas analysis!

- Proven sensor technologies
- Fast & easy installation
- Low cost operation / maintenance
- Value price

THE COMPLETE, READY TO USE

emissions analyzer SWG 100 CEM is the low cost solution to be used with a wide variety of industrial emissions monitoring applications:

- cogeneration heat and power engines (CHP)
- small power plants, small gas turbines
- waste incinerators, ovens and kilns
- ethanol and palm oil plants and more
- food industry steam boilers
- bio methane and methane boilers
- industrial heaters and dryers

SWG 100 - CEM - Instrument main features are:

- field replaceable, plug & play pre-calibrated sensors
- very compact industrial design, for up to 6 gas simultaneous measurement
- use low cost but reliable electrochemical cells for O₂, CO, NO, NO₂, SO₂
- and infrared module (NDIR) for CO₂ measurement
- advanced sample gas preparation for fast and reliable measurements
- flexible platform can be used for various combustion applications
- direct and continuous/discontinuous measurement, with pressure and temperature
- compensation of all main flue gas parameters
- external measurements (temperature, pressure, etc.) by reading of ext. standard signal
- simple installation, ready to run delivery and easy to maintain

Auto-Zero and Auto-Cal solenoid valves

Sample gas inlet with heated or unheated gas sampling line

Gas cooler (Peltier type)

EC cells for O₂
CO; NO; NO₂; SO₂

Gas sampling pump

CO₂ NDIR

Condensate draining pump

Cut-off and purge for CO

Internal sample flow monitoring

Optional: cabinet heater


Main PCB

Continuous monitored ventilation fan with alarm


Universal power supply
90 - 240 Vac 47 - 63 Hz / 90 W

Modules with analog outputs 4 channel 4-20 mA, RS 485 and 2x alarm relays

Direct instant keypad and bright display



Customizable display with 6 or 2 values per screen



OPTIONAL with AUTO-Calibration



OPTIONAL with gas cooler



Field replaceable pre-calibrated sensors




THE MRU SWG 100 CEM

continuous emission monitoring analyzer, is designed for use in the harsh industrial environment of different combustion sites, where flue gas emissions must be continuously monitored.

The analyzer can be installed in outdoor or indoor locations, can sample dry or wet flue gas, pressurized or low pressure flue gas, even from a long distance sampling point.

The analyzer system can be configured with different gas sampling probes and sampling lines to optimize the sample gas preparation.

SWG 100 - CEM	standard	option
Basic analyzer for wall or rack mounting, IP54 protection, aluminum cabinet with anti-corrosive red structural lacquer and fan ventilation	●	
Condensate separator and automatic condensate draining pump	●	
Monitored ambient air ventilation, with alarm display for fan rotation failure	●	
Sample gas pump and internal sample flow monitoring with alarm in case of filter clogging	●	
Solenoid valve for auto-zero with ambient air and for auto-calibration with span gas	●	
1/8" threads for all sample gas, zero gas and calibration gas inlets, fittings for DN6/4mm tube	●	
3.5" TFT color, backlit display and keyboard, password protected operation	●	
RS485 digital data transfer (Modbus RTU)	●	
Universal power supply 90 - 240 Vac / 47-63 Hz / 90 W	●	
O ₂ measurement with long-life EC cell		●
CO measurement with protected EC cell using cut-off solenoid valve and air purging pump		●
NO measurement with EC cell		●
NO ₂ measurement with EC cell		●
SO ₂ measurement with EC cell		●
CO ₂ measurement using infrared (NDIR) module		●
Thermoelectric gas cooler (Peltier) with constant dew point and automatic condensate draining pump		●
Heated gas sampling probe model HD, with ceramic filter and back-purge, for flying ash type flue gases		●
Heated gas sampling probe model HD-GW, with quartz glass wool filter for acid mist flue gases		●
Unheated gas sampling probe model LD, for clean combustions, using in-situ sintered metal filter		●
Heated gas sampling lines, from 5 to 75 m length, with temperature regulation by analyzer or by internal thermostat, with single or dual PTFE 4/6 mm tube		●
Module with 4 channel analog outputs/inputs 4-20 mA, with 2x "fail safe" alarm relays		●
Converter module of RS485 into Profibus		●
Cabinet heater for freeze protection		●



TECHNICAL SPECIFICATIONS

Measurement components	Measuring range	Accuracy	Measuring method
O ₂ Oxygen	0 ... 25 %	0.2 % abs.	electrochemical
CO Carbon monoxide	0 ... 10,000 ppm	±10 ppm or 3 % reading	electrochemical
NO Nitric oxide	0 ... 4,000 ppm	± 5 ppm or 3 % reading	electrochemical
NO ₂ Nitrogen dioxide	0 ... 1,000ppm	± 5 ppm or 3 % reading	electrochemical
SO ₂ Sulfur dioxide	0 ... 4,000ppm	±10 ppm or 3 % reading	electrochemical
CO ₂ Carbon dioxide	0 ... 40 %	±0,3 % or 3 % reading	NDIR

Zero drift	Negligible with automatic zeroing
Drift	Less 0.2 % of range per month

Calculated component	<p>True NO_x : NO + NO₂</p> <p>Calc. NO_x = 1.05*NO (if NO₂ is not measured)</p> <p>All emissions relevant mg/Nm³; user selectable O₂ referencing</p> <p>Combustion efficiency (fuel type depending), heat loss, dewpoint</p>
----------------------	---

HMI human machine interface	<p>3.5" TFT color and backlit display</p> <p>Keyboard and password protected operation</p> <p>I/O module with 4channel, analog out 4-20 mA, floating, max. load 500 R</p> <p>and 2 alarm relays, potential free contacts 24 Vdc/5 A</p> <p>SD-card for data and event logging</p> <p>RS485 digital interface (Modbus RTU)</p> <p>DIN-rail RS485 / ProfiBus converter</p>
-----------------------------	--

Sample preparation	<p>Gas sampling probe HD, heated ceramic filter with back-purge, or gas sampling probe HD-GW, heated quartz wool filter, or gas sampling probe LD, non-heated with in-situ sintered filter</p> <p>Heated or non-heated DN4/6 mm PTFE sampling line</p> <p>Thermoelectric gas cooler (Peltier type) with constant 41°F (+5 °C) dewpoint</p> <p>Teflon particulate filter, internal Viton hosing</p> <p>Controlled and regulated gas sampling pump</p> <p>Constant gas sample flow of 50 l/h</p> <p>Sample inlet pressure: -80 inH₂O to 80 inH₂O (-200 mbar to +200 mbar)</p> <p>Sample venting: atmospheric pressure</p>
--------------------	---

Cabinet dimensions	Aluminum with anti-corrosive structural painting
Weight / Protection	27.55" x 23.61" x 8.26" (700 x 600 x 210 mm) (H x W x D) for wall or rack mounting
Ambient temperature	55lbs (25kg) / IP54
Installation site	41°F...113°F standard, 41°F...131°F with Vortec cooler, 14°F...113°F with cabinet heater
Cabinet conditioning	+5°C...+45°C standard, +5°C...+55°C with Vortec cooler, -10°C...+45°C with cabinet heater
Power supply	Indoor or outdoor (rain and sun shade is mandatory user scope of supply)
	Continuous, monitored fan ventilation
	Cabinet heater 200 W
	Cabinet Vortec cooler (requires 0,5m ³ /min clean and dry compressed air)
	Universal 90 - 240 Vac / 47 - 63 Hz / 90 W (300 W with cabinet heater)

Data subject to change without notice

MRU Instruments, Inc.
Houston, Texas 77044
Tel.: (832) 230 - 0155
Fax: (832) 230 - 1553
info@mru-instruments.com
www.mru-instruments.com

Support and sales by:

